

IOT-L2-2

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe.
Quad-core A53, 1GB RAM, 2LAN, 1 USB, *USB-C power supply**

***Power supply for IOT linker is offered separately**



Order code without software	IOT-L2-2
Order code with S-RMS software	IOT-L2-2-SRMS
Order code with HEMS software	HEMS-GW
Order code AC Power Supply 230VAC/5VDC (Schuko Plug - USB-C)	IOT-PS-PLUG-USB
Order code DC Power Supply 24VDC/5VDC (Converters)	IOT-PS-DC-USB
4G LTE USB modem for IOT linker	IOT-L2-W
Mounting:	DIN rail (or wall)
Dimensions:	60 x 61 x 26 mm
Connection:	LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

Application

Software Code	Description
HEMS Software	RDC Charger, HEMS
IOT-L2-2-SRMS	Web UI for room management system (hotels, offices etc.) API for integration with 4S and other cloud solutions. S-RMS software includes S-Access software as well.
Custom Software	Custom projects (Connection of Cybro to HIQ Universe, Web user interface for control and supervision etc...)

Note: The device is available with or without software. The final price depends on the selected software package and required system configuration.

Technical specifications

Power supply:	USB-C, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 80°C
4G connection :	USB LTE Modem (Order code IOT-L2-W)