



RDC Charger

User manual



Robotina d.o.o.
OIC-Hrpelje 38 Hrpelje
SI-6240 Kozina
Slovenia

Table of Contents

| | |
|---------------------------------------|---|
| Electric strike | 5 |
| General description | 5 |
| Technical specifications | 6 |
| Dimensions | 6 |
| Terminals | 6 |

Electric strike

Electromechanical strike lock

Model number:

EL-ST



General description

The most compact electric strike without sacrificing any of the quality or safety offered by our other products. EL-ST is the perfect match for narrow aluminium, PVC or timber profiles.

Technical specifications

| | |
|---|--------------------------------------|
| Power supply: | 9-24V AC/DC, 12V DC |
| Continuos duty: | <1 min/ED 100% |
| Rated resistance: | 43 Ohm |
| Current consumption AC: | 0.15A...9V, 0.2A...12V, 0.39A...24V |
| Current consumption DC(stabilized): | 0.21A...9V, 0.28A...12V, 0.56A...24V |
| Maximum side-load on AC: | 24V - 200N |
| Maximum side-load on DC (stabilized): | 12V - 50N |
| Break-in resistance: | 4.800N |
| Dynamic strength: | 4.400N |
| Endurance rating (cycles no side-load): | 200.000 |
| Complies with the directive: | 2014/30/UE; 2011/65/UE |

Dimensions



Terminals

