

eSTORE 512-2800-75-O

LiFePO4 HV battery rack + 75kW HV inverter



Order code:	eSTORE 512-2800-60-O
Order code HV inverter:	HV-75-3P-01
Description:	High performance battery pack
Technology:	LiFePO4
Cell:	Grade A prismatic cell
Cycles:	Over 6500 cycles with 80% DoD
Rack batteries:	RB 512-280-R
BMS:	High end BMS
Compatibility:	Robotina xEMS, Modbus

Features

Industry grade ESS with high energy and power density, scalability and excellent performance. When

integrated with Robotina xEMS, this LiFePO4 battery implements client's energy strategy.

Technical specification for battery

Nominal capacity:	143.36kWh
Nominal voltage:	512V
End of discharge voltage:	460V
Charging voltage:	560V
Continuous Charge I:	150A
Continuous Discharge I:	150A
Peak Charge/Discharge I:	200A
Internal impedance:	>10mOhm
Charge temperature:	0..45°C
Discharge temperature:	-10..55°C
Parallel Connection:	up to 10 (more optional)
MBS communication:	CAN/S485
Self discharge:	<2.5%/Mo
Weight:	1500kg
Dimensions (WxHxD):	1300x1220x980mm
Installation method:	floor-standing
Environment:	Outdoor IP54
Air conditioning:	1.5 kW, DC power

Technical specification for inverter

AC output data

Rated output power of AC and UPS (W):	75000
Rated AC Input/Output current(A) :	113.7/108.7
Max AC Input/Output current(A):	125/119.6
Output frequency and voltage:	50/60Hz; 230Vac/400Vac (3 phases)

PV input data

Max DC input power (W):	120000
PV input voltage (V):	1000
Starting voltage (V):	180
PV input current (A):	36+36+36+36+36+36

Connected battery input data

Battery voltage range (V):	160-1000
Max charging current (A):	80+80
Max discharging current (A):	80+80

General technical data

Working temperature (°C):	-40 ~ 60
Communication with BMS:	RS485,RS232, CAN
Weight (kg):	97,5
Degree of protection (IP):	IP65

Dimensions

