

# IOT-L2-2

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe.  
 Quad-core A53, 1GB RAM, 2LAN, 1 USB, \*USB-C power supply**

**\*Power supply for IOT linker is offered separately**



Order code custom software	<b>IOT-L2-2</b>
Order code HEMS software	<b>HEMS-GW</b>
Order code AC Power Supply 230VAC/5VDC	<b>IOT-PS-AC</b>
Order code DC Power Supply 24VDC/5VDC	<b>IOT-PS-DC</b>
4G LTE USB modem for IOT linker	<b>IOT-L2-W</b>

Mounting:	DIN rail (or wall)
Dimensions:	60 x 61 x 26 mm
Connection:	LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

## Application

\* RDC Charger, HEMS \* Custom projects (Connection of Cybro to HIQ Universe, Web user interface for control and supervision etc...)

## Technical specifications

Power supply:	USB-C, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 80°C
4G connection :	USB LTE Modem (Order code IOT-L2-W