

IOT-L2-2

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe.
 Quad-core A53, 1GB RAM, 2LAN, 1 USB, *USB-C power supply**

***Power supply for IOT linker is offered separately**



Order code custom software	IOT-L2-2
Order code HEMS software	HEMS-GW
Order code AC Power Supply 230VAC/5VDC	IOT-PS-AC
Order code DC Power Supply 24VDC/5VDC	IOT-PS-DC
4G LTE USB modem for IOT linker	IOT-L2-W

Mounting:	DIN rail (or wall)
Dimensions:	60 x 61 x 26 mm
Connection:	LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

Application

HEMS Software	RDC Charger, HEMS
Custom Software	Custom projects (Connection of Cybro to HIQ Universe, Web user interface for control and supervision etc...)
HEMS Software	RDC Charger, HEMS
Custom Software	Custom projects (Connection of Cybro to HIQ Universe, Web user interface for control and supervision etc...)

Technical specifications

Power supply:	USB-C, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 80°C
4G connection :	USB LTE Modem (Order code IOT-L2-W