

IOT-L3-3

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe.
 Quad-core Cortex A55 CPU, 4GB RAM, 3x Ethernet, 2xUSB, *USB-C Power Supply**

***Power supply for IOT linker is offered separately**



Order code	IOT-L3-3
Order code AC Power Supply 230VAC/5VDC	IOT-PS-AC
Order code DC Power Supply 24VDC/5VDC	IOT-PS-DC
4G LTE USB modem for IOT linker	IOT-L3-W
Mounting:	DIN rail
Dimensions:	94.5 x 68 x 30 mm

Connection:	LAN Port: connects to Cybro, MC Controller or RDC Charger; WAN Port: uplink to HIQ Universe
-------------	---

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

Technical specifications

Power supply:	USB-C, 5V DC
Storage:	32GB eMMC, support for NVME M.2 2280 SSD
USB Host:	2x USB 3.0 Type-A ports
Network:	Native Gigabit Ethernet x1, PCIe 2.5Gbps Ethernet x2
Working temp.:	0°C to 70°C
4G connection :	LTE USB modem for IOT linker (Order code IOT-L3-W)