

# IOT-L3-PRO

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe. Octo-core CPU (4x Cortex A76, 4x Cortex A55) , 4GB RAM (8GB or 16GB optional), 2x Ethernet, 1 USB, \*12V Power Supply**

**\*Power supply for IOT linker is offered separately**



Order code with custom software	<b>IOT-L3-PRO</b>
Order code with BM-GW software	<b>01_bm-gw</b>
Mounting	DIN rail
Dimensions	86 x 114 x 30 mm
Connection	ETH1 Port: uplink to HIQ Universe; ETH2 Port: connects to Cybro, MC Controller or RDC Charger

Power supply Order code	<a href="#">PS-30-12</a>
-------------------------	--------------------------

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

## Application

<b>BM-GW Software</b>	Web UI monitoring batteries of large UPS systems (data centers, comercial systems)
<b>Custom Software</b>	Only for some cases when the linkers IOT-L2-2 and IOT-L3-3 are not powerful enough

## Technical specifications

Power supply:	12V DC (Barrel Connector 5.5mm x 2.1mm)
Storage:	0GB/32GB/64GB/256GB eMMC, NVME M.2 2280 SSD up to 2500 MB/s
USB Host:	1 x USB 3.0 Type A, 1 x USB-C: Full function USB Type-C
Network:	ePCIe 2.5Gbps Ethernet x2, PCIe 2.1 x 1 and USB2.0 Host support for M.2 WiFi and Bluetooth Module
Working temp.:	0°C to 70°C
4G connection :	MiniPCIe modem card, SIM Card slot on board