

## **RBHV 665-100-RA-O**

## LiFePO4 HV battery rack



Order code:	RBHV 665-100-RA-0
Description:	High performance battery pack
Technology:	LiFePO4
Cell:	Grade A prismatic cell
Cycles:	Over 6500 cycles with 80% DoD
Rack batteries:	RB 512-100-R
BMS:	High end BMS
Compatiility:	xEMS, Deye-R, other inverters

## **Features**

Industry grade ESS with high energy and power density, scalability and excellent performance. When

(c) Robotina d.o.o.

integrated with Robotina xEMS, this LiFePO4 battery implements client's energy strategy.

## **Technical specification**

Nominal capacity:	66.5kWh
Nominal voltage:	665V
End of discharge voltage:	570V
Charging voltage:	760V
Continuous Charge I:	100A
Continuous Discharge I:	100A
Peak Charge/Discharge I:	150A
Internal impedance:	>10mOhm
Charge temperature:	045°C
Discharge temperature:	-1050°C
Parallel Connection:	up to 20
MBS communication:	CAN/S485
Self discharge:	<2.5%/Mo
Weight:	850kg
Dimensions (WxHxD):	700x2250x700mm
Installation method:	floor-standing
Environment:	Outdoor
Air conditioning:	1.5 kW, DC power

(c) Robotina d.o.o. 2/3

(c) Robotina d.o.o. 3/3