



RDC Charger

User manual



Robotina d.o.o.
OIC-Hrpelje 38 Hrpelje
SI-6240 Kozina
Slovenia

Table of Contents

BM-MC	5
<i>Highlights & Features</i>	5
<i>Technical specification</i>	5
<i>Wiring</i>	6

BM-MC

BTMS Master controller



Order code:	BM-MC
Mounting:	DIN rail, 6M, 106 mm
Dimensions:	106×108×58 mm

Highlights & Features

- Communication with temperature and humidity sensors
- Additional digital inputs for connecting various sensors (leakage, gas,...)
- Additional digital outputs for disconnecting strings with an error or for alarming
- Supports up to:
 - 32 strings (BM-SS)
 - 4 Digital IO modules (BM-LC) with 8 DI and 8 DO each

Technical specification

Power supply	Nominal	24 VDC
	Range	18 .. 28 VDC
Power consumption	Typical	150 mA
	Max	280 mA
Digital outputs	relay 8A/250VAC or 8A/30VDC resistive	
Operating conditions	0..50°C, 0..85% rh non-condensing	
Dimensions	width	185 (110+2×37,5) mm
	height	103 mm
	depth	51 mm

LED indicators

PWR		power supply OK
RUN		run
		stop
		pause
		program error
		no kernel
		hardware error
IEX2	IEX-2 modules communication status	
COM1	BM-TP communication status	
COM2	BM-SS communication status	
Ethernet	LAN communication status	

Wiring

