



# RDC Charger

## User manual



**Robotina d.o.o.**

OIC-Hrpelje 38 Hrpelje  
SI-6240 Kozina  
Slovenia



# Table of Contents

**TH-MC** ..... 5  
***Highlights & Features*** ..... 5  
***Technical specification*** ..... 5  
***Wiring*** ..... 6



# TH-MC

## Temperature and humidity monitoring Master controller



Order code:	<b>TH-MC</b>
Mounting:	DIN rail, 6M, 106 mm
Dimensions:	106×108×58 mm

## Highlights & Features

- Communication with temperature and humidity sensors
- Supports up to:
  - 120 Temperature-humidity sensors (BM-TH)

## Technical specification

<b>Power supply</b>	Nominal	24 VDC
	Range	18 .. 28 VDC
<b>Power consumption</b>	Typical	150 mA
	Max	280 mA
<b>Digital outputs</b>	relay 8A/250VAC or 8A/30VDC resistive	
<b>Operating conditions</b>	0..50°C, 0..85% rh non-condensing	

<b>Dimensions</b>	width	185 (110+2×37,5) mm
	height	103 mm
	depth	51 mm

### LED indicators

<b>PWR</b>		power supply OK
<b>RUN</b>		run
		stop
		pause
		program error
		no kernel
		hardware error
<b>IEX2</b>	IEX-2 modules communication status	
<b>COM1</b>	-	
<b>COM2</b>	BM-TH communication status	
<b>Ethernet</b>	LAN communication status	

### Wiring

