



RDC Charger

User manual



Robotina d.o.o.
OIC-Hrpelje 38 Hrpelje
SI-6240 Kozina
Slovenia

Table of Contents

BM-AG 5
Highlights & Features 5
HW Technical specification 5
Wiring 5

BM-AG

BTMS IOT Agregator



Order code:	BM-AG
Mounting:	DIN rail, 31 mm
Dimensions:	31 x 125 x 100 mm

Highlights & Features

- It logically combines several BM-GWs into one system
- Overview of the entire Data Center via a single web interface

HW Technical specification

Power supply:	12 to 24 VDC, 1.39-0.72A	
Construction:	Extruded aluminum and heavy-duty steel, IP30	
CPU:	Intel® Celeron® N3350 2C @1.1 GHz, TDP: 6W	
System Memory:	1 x DDR3L-1866 SO-DIMM 4 GB	
Storage:	128 GB SSD	
System I/O Outlet:	Serial 1 x DB9 RS-232/422/485	
	Display 1 x VGA	
	Ethernet 2 x RJ-45 isolated* 10/100/1000 Mbps	
	DIO 1 x DB9 8-bit programmable DIO	
	LTE Cat 4 Quectel EG25-G Mini PCIe	
Working temp.:	-20°C to +70°C (-4°F to +158°F)	
Humidity:	0% to 95%	
Vibration Endurance:	2 Gms with storage (5 to 500Hz, X/Y/Z direction; random, operating)	
Mounting:	DIN rail, wall	
Weight (net/gross):	0.3 kg (0.67 lb)/0.45 kg (0.99 lb)	
Dimensions:	height	125 mm
	width	31 mm
	depth	100 mm



Wiring

