

# IOT-L3-3

**Advanced EDGE device. Connects Cybro, MC Controller and RDC Charger to HIQ universe.  
 Quad-core Cortex A55 CPU, 4GB RAM, 3x Ethernet, 2xUSB, USB-C Power Supply**



Order code without Power Supply	<b>IOT-L3-3</b>
Order code with AC Power Supply 230VAC/5VDC	<b>IOT-L3-3-AC</b>
Order code with DC Power Supply 24VDC/5VDC	<b>IOT-L3-3-DC</b>
4G LTE USB modem for IOT linker	<b>IOT-L3-W</b>
Mounting:	DIN rail
Dimensions:	94.5 x 68 x 30 mm

Connection:	LAN Port: connects to Cybro, MC Controller or RDC Charger; WAN Port: uplink to HIQ Universe
-------------	---

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

## Technical specifications

Power supply:	USB-C, 5V DC
Storage:	32GB eMMC, support for NVME M.2 2280 SSD
USB Host:	2x USB 3.0 Type-A ports
Network:	Native Gigabit Ethernet x1, PCIe 2.5Gbps Ethernet x2
Working temp.:	0°C to 70°C
4G connection :	LTE USB modem for IOT linker (Order code IOT-L3-W)